

# Hose Type I0/6

ID10 - Series: C



## Applications


- Waterblast:** Surface preparation (concrete removal, surface cleaning of buildings, paint removal), tank and vessel cleaning, ultra high-pressure waterjet cutting and hydro demolition (cutting and demolition of armoured concrete, pipelines, paper or steel)
- Hydraulics:** Pressure test equipment (valves, tooling and control panels)




## Technical Information


- Inner Core:** Polyoxymethylene (POM)
- Pressure Support:** 6 layers of high-tensile steel wire
- Outer Cover:** Polyamide (PA)
- Colour:** Blue
- Temperature:** -30°C to +60°C [-22°F to 140°F]

Ø ID	Ø OD	Working Pressure (SF 2,5:1)	Burst Pressure	Bend Radius	Weight	Insert ID
9,8 mm	20,4 mm	1.920 bar	4.800 bar	250 mm	1,000 kg/m	5,5 mm
0,39 inch	0,80 inch	27.840 psi	69.600 psi	9,84 inch	0,672 lbs/ft	0,22 inch

Part no.	Thread	Material	Dimensions (mm)				Sleeve
			A	B	C	⚙	
<b>Sleeve</b>							
11060102	-	Steel	26,6	64	-	-	

Part no.	Thread	Material	Nut	Dimensions (mm)				Insert
				A	B	C	⚙	
<b>HP fitting</b>								
41060204C	9/16"x18UNF LH	Stainless steel	-	5,5	114	24	-	

<b>Female swivel 24°/60°</b>								
21060304C	G1/2"	Stainless steel	51060311	5,5	78	-	27	

<b>Female swivel with O-Ring</b>								
21060204C	M22x1.5	Stainless steel	51060201, 51060205	5,5	90	-	30	
21060224C	M24x1.5	Stainless steel	51320205, 51321206	5,5	93	-	32	