

Hose Type 13/2WR

Silver Mongoose

ID13 - Series: O



Applications

- Waterblast:** Heat exchanger tube cleaning, surface preparation (concrete removal, surface cleaning of buildings, paint removal)
- Hydraulics:** Pressure test equipment (valves, tooling and control panels)
- Oil and Gas:** Grease injection, nitrogen service, Gaseous media handling



Technical Information

- Inner Core:** Polyamide (PA)
- Pressure Support:** 2 open layers, 2 dense layers of high-tensile steel wire
- Outer Cover:** Polyurethane (PUR)
- Colour:** Silver
- Temperature:** -30°C to +60°C [-22°F to 140°F]

Ø ID	Ø OD	Working Pressure (SF 2,5:1)	Burst Pressure	Bend Radius	Weight	Insert ID
12,8 mm	22,2 mm	1.040 bar	2.600 bar	150 mm	0,590 kg/m	7,5 mm
0,50 inch	0,87 inch	15.080 psi	37.700 psi	5,91 inch	0,395 lbs/ft	0,30 inch

Part no.	Thread	Material	Dimensions (mm) A B C	⚙	Sleeve
Sleeve					
I1330206VVR	-	Steel	27,5 64 - -		
I1330205VVR	-	AISI 316Ti	27,5 60 - -		

Part no.	Thread	Material	Nut	Dimensions (mm) A B C	⚙	Insert
MP fitting						
41360205O	9/16"x18UNF LH	AISI 316Ti	-	7,5 118 13	-	

Male fitting						
31360401O	1/2"x14NPTF	Steel	-	7,5 99 18 22		
31360405O	1/2"x14NPTF	AISI 316Ti	-	7,5 99 18 22		



Female swivel 24°/60°						
21360332O	G1/2"	Steel	51060311	7,5 81 - 27		
21360335O	G1/2"	AISI 316Ti	51060315	7,5 81 - 27		


Hose Type I3/2WR

Silver Mongoose

ID13 - Series: O



Part no.	Thread	Material	Nut	Dimensions (mm)				Insert
				A	B	C		
Female swivel with O-Ring								
21360122O	M22x1.5	Steel	51360221	7,5	97	-	30	
21360242O	M24x1.5	Steel	51321206	7,5	89	-	32	
21360245O	M24x1.5	AISI 316Ti	51320205	7,5	89	-	36	
Type M female swivel								
21360642O	1"x12UNF	Steel	51360641	7,5	84	-	32	
21360645O	1"x12UNF	AISI 316Ti	51360645	7,5	84	-	32	

Part no.	Thread	Material	Relief bores	Dimensions (mm)				Swivel nut
				A	B	C		
Swivel nut								
51360641	1"x12UNF	Steel	1 radial	16,8	28	22	32	
51360645	1"x12UNF	AISI 316Ti	1 radial	16,8	28	22	32	
51060311	G1/2"	Steel	1 radial	16,7	23,5	13,5	27	
51060315	G1/2"	AISI 316Ti	1 radial	16,7	23,5	13,5	27	
51360221	M22x1.5	Steel	1 radial	16,8	25	14	30	
51321206	M24x1.5	Steel	2 axial	16,8	23	16	32	
51320205	M24x1.5	AISI 316Ti	1 radial	16,8	23	16	32	

Hose Type I3/2WR

Silver Mongoose

ID13 - Series: O



Part no.	Size (mm)	Material	Crimp ring	Hose protection
Hose protection without spiral				
I.903037	ID Ø30, OD Ø39	PVC	I003941	
I.903542	ID Ø35, OD Ø42	PVC	-	
Hose protection with spiral				
I.913038	ID Ø30, OD Ø38	PVC	I004145	
I.913240	ID Ø32, OD Ø40	PVC	-	

Part no.	Mesh length (mm)	Overall length (mm)	Breaking strength (kN)	Suitable for SPIR STAR® hose outer diameter (mm)	Hose securing grip
Hose securing grip short version					
9106400	600,00	800,00	20,40	20-25	

Accessories combinations					
Without hose protection					
Description		Bend restrictor	Crimp ring	Securing grips	
Securing grip		-	-	9106400	
Hose protection without spiral					
Description	Protection hose	Bend restrictor	Crimp ring	Securing grips	
Protection hose	I.903037	-	I003941	-	
with securing grip	I.903542	-	-	9106400	
Hose protection with spiral					
Description	Protection hose	Bend restrictor	Crimp ring	Securing grips	
Protection hose	I.913038	-	I004145	-	
with securing grip	I.913240	-	-	9106400	

Production-related variations of the burst pressure of up to 5 % are possible. Other colours upon request.

The safety factors between the burst pressure and the working pressure as well as the test pressure depend on the operating conditions. For gaseous media the outer cover is to be pinpricked.

Regarding the safety factor for gaseous media please contact your local SPIR STAR® assembling center.

The indicated working pressure refers to the hose only. Depending on the used fitting the permitted working pressure of a hose assembly may be less.

*) Blast-Pro® fittings may only be used for tube cleaning operations inside the tube. They have not been designed for the use outside of tubes.

We reserve our rights for technical changes without notice. Subject to printing errors.