

Hose Type 8/2 PA

DuraLife Flex ®

ID8 - Series: A and X



Applications


- Waterblast:** Surface preparation (concrete removal, surface cleaning of buildings, paint removal)
- Hydraulics:** Pressure test equipment (valves, tooling and control panels)





Technical Information

- Inner Core:** Polyamide (PA)
- Pressure Support:** 2 layers of high-tensile steel wire
- Outer Cover:** Polyamide (PA)
- Colour:** Blue
- Temperature:** -30°C to +60°C [-22°F to 140°F]

Ø ID	Ø OD	Working Pressure (SF 2.5:1)	Burst Pressure	Bend Radius	Weight	Insert ID
8,1 mm	13,3 mm	840 bar	2.100 bar	130 mm	0,200 kg/m	5,5 mm
0,32 inch	0,52 inch	12.180 psi	30.450 psi	5,12 inch	0,134 lbs/ft	0,22 inch

Part no.	Thread	Material	Dimensions (mm)				Sleeve
			A	B	C	⚙	
Sleeve							
10820101	-	Steel	17,8	49	-	-	

Part no.	Thread	Material	Nut	Dimensions (mm)				Insert
				A	B	C	⚙	
Male fitting								
30820411A	1/4"x18NPTF	Steel	-	5,5	68	14	14	
30820401A	3/8"x18NPTF	Steel	-	5,5	69	14	17	
Male fitting 60° internal cone								
30820321A	G1/4"	Steel	-	5,5	63	12	14	
30820301A	G3/8"	Steel	-	5,5	65	12	17	

Hose Type 8/2 PA

DuraLife Flex ®

ID8 - Series: A and X



Part no.	Thread	Material	Nut	Dimensions (mm)				Insert
				A	B	C	⚙	

Male fitting flat seal

30820381A	G1/4"	Steel	-	5,5	70	15	12	
-----------	-------	-------	---	-----	----	----	----	--

Male fitting DIN3852 T2 form A

30820341A	G3/8"	Steel	-	5,5	69,5	14,5	22	
-----------	-------	-------	---	-----	------	------	----	--

Part no.	Thread	Material	Hose part	Dimensions (mm)				OnePiece Fittings®
				A	B	C	D	

OnePiece Fittings®

30820461X	1/4"x18NPTF	Steel	30820441/1X	5,5	39	14	17,5	
30820441X	3/8"x18NPT	Steel	30820441/1X	5,5	38	14	17,5	

Part no.	Thread	Material	Nut	Dimensions (mm)				Insert
				A	B	C	⚙	

Female swivel 24°/60°

20820301A	G3/8"	Steel	50860301	5,5	62	-	24	
-----------	-------	-------	----------	-----	----	---	----	--

Female swivel with O-Ring

20820201A	M20x1.5	Steel	50860201	5,5	65	-	27	
20820042A	M24x1.5	Steel	51321206	5,5	75	-	32	

Hose Type 8/2 PA

DuraLife Flex ®

ID8 - Series: A and X



Part no.	Thread	Material	Nut	Dimensions (mm)				Insert
				A	B	C	⌀	
Type M female swivel								
20820645A	3/4"x16UNF	AISI 316Ti	50840605, 50840601	5,5	62	-	24	
JIC female swivel								
20820601A	9/16"x18UNF	Steel	50820601	5,5	56	-	19	
20820605A	9/16"x18UNF	AISI 316Ti	50820605	5,5	56	-	19	

Part no.	Thread	Material	Relief bores	Dimensions (mm)				Swivel nut
				A	B	C	⌀	
Swivel nut								
50820601	9/16"x18UNF	Steel	1 radial	10,6	18	14	19	
50820605	9/16"x18UNF	AISI 316Ti	1 radial	10,6	18	14	19	
50840601	3/4"x16UNF	Steel	1 radial	12,2	22,5	17,5	24	
50840605	3/4"x16UNF	AISI 316Ti	1 radial	12,2	22,5	17,5	24	
50860301	G3/8"	Steel	1 radial	12,5	21,5	15,5	24	
50860201	M20x1.5	Steel	1 radial	12,2	22	12	27	
51321206	M24x1.5	Steel	2 axial	16,8	23	16	32	

Part no.	Mesh length (mm)	Overall length (mm)	Breaking strength (kN)	Suitable for SPIR STAR® hose outer diameter (mm)	Hose securing grip
Hose securing grip short version					
9056400	600,00	740,00	10,20	10-15	

Production-related variations of the burst pressure of up to 5 % are possible. Other colours upon request.

The safety factors between the burst pressure and the working pressure as well as the test pressure depend on the operating conditions. For gaseous media the outer cover is to be pinpricked.

Regarding the safety factor for gaseous media please contact your local SPIR STAR® assembling center.

The indicated working pressure refers to the hose only. Depending on the used fitting the permitted working pressure of a hose assembly may be less.

*) Blast-Pro® fittings may only be used for tube cleaning operations inside the tube. They have not been designed for the use outside of tubes.

We reserve our rights for technical changes without notice. Subject to printing errors.