## LOW PRESSURE CONNECTION COMPONENTS & TUBING

## Tubing

Catalog				
Number	Connection	O.D.	I.D.	MAWP
LP062-031-*	1/16" L/P	0.062"	0.031"	15,000 PSI
		(1.6)	(0.8)	1030 bar
LP125-062-*	1/8" L/P	0.125"	0.062"	15,000 PSI
		(3.2)	(1.6)	1030 bar
LP250-125-*	1/4" L/P	0.250"	0.125"	11,500 PSI
		(6.4)	(3.2)	790 bar
LP375-250-*	3/8" L/P	0.375"	0.250"	7,500 PSI
		(9.5)	(6.4)	520 bar
LP500-334-*	1/2" L/P	0.500"	0.334"	7,000 PSI
		(12.7)	(8.5)	480 bar
LP500-375-*	1/2" L/P	0.500"	0.375"	5,500 PSI
		(12.7)	(9.5)	380 bar

\*Complete catalog number by adding suffix **316** for 316 stainless steel or suffix **304** for 304 stainless steel. Other materials are also available, please consult factory.

BuTech Pressure Systems offers a complete selection of annealed seamless stainless steel tubing for high pressure applications where both high strength and corrosion resistance are desired. Tubing is available in standard 20-24 foot lengths (6-7 meters), however, longer lengths are available on request.



See Section T for Tube Benders and Tube Vises!



All dimensions are for reference only and are subject to change. Dimensions in parentheses are millimeters (mm) Page LP-9

