

BSPP Adapters

SPIR STAR BSPP fittings are available with both internal and external sealing cones.

Ext	120 degree external sealing cone
Int	60 degree internal sealing cone

Please note that when sealing BSPP adapters with bonded seals rather than on the cone, the working pressure of the fitting may be lower than the working pressure stated on the fitting.

BSPP Adapters		
Part Number	Description	Max Working Pressure
C09-125-1680	1/4" MBSPP-Ext. x 1/4" HP Male	2,068 bar / 30,000 psi
C09-125-1681	1/4" MBSPP-Ext. x 1/4" MP Male	1,380 bar / 20,000 psi
C19-950-0029	1/4" MBSPP-Ext. x 9/16"-18 Type M Male	2,068 bar / 30,000 psi
C19-950-1601	1/4" MBSPP-Ext. x 1/4" MBSPP-Ext.	2,068 bar / 30,000 psi
C19-950-1602	1/4" MBSPP-Ext. x 1/4" MBSPP-Int.	2,068 bar / 30,000 psi
C19-950-1622	1/4" MBSPP-Int. x 1/4" MBSPP-Int.	2,068 bar / 30,000 psi
C19-950-1623	1/4" MBSPP-Int. x 1/4" NPT Male	1,035 bar / 15,000 psi
C19-950-1624	1/4" MBSPP-Int. x 1/2" NPT Male	1,035 bar / 15,000 psi
C19-950-1625	1/4" MBSPP-Ext. x 1/4" NPT Male	1,035 bar / 15,000 psi
C19-950-1680	1/4" BSPP Female Cross	2,068 bar / 30,000 psi
C19-950-1681	1/4" BSPP Female Tee	2,068 bar / 30,000 psi
C19-950-HEBM4	1/4" MBSPP-Ext. Elbow	2,068 bar / 30,000 psi
C19-950-PLUG	1/4" MBSPP-Ext. Plug	2,068 bar / 30,000 psi
C19-950-0062	1/4" BSPP Bonded Seal	1,000 bar / 14,500 psi
C19-950-0083	1/4" BSPP Bonded Seal	1,500 bar / 21,750 psi



BSPP Male Connectors-int.		
Part Number	Description	Max Working Pressure
HBM4-BM4	G1/4" Male Connector	2,800 bar / 40,600 psi
HBM6-BM6	G3/8" Male Connector	2,800 bar / 40,600 psi
HBM8-BM8	G1/2" Male Connector	2,000 bar / 29,000 psi

