



High Pressure Adapters

6YY6 — Female High Pressure x Male High Pressure




Part Number	T1 Thread Size	T2 Thread Size	A Overall Length		H Hex		Max. Working Pressure	
			inch	mm	inch	mm	psi	MPa
#								
6YY6-4-6C	9/16" - 18 UNF	3/4" - 16 UNF	1.75	44.45	0.75	19.05	60,000	414
6YY6-4-9C	9/16" - 18 UNF	1-1/8" - 12 UNF	2.12	53.85	1.12	28.45	60,000	414
6YY6-6-4C	3/4" - 16 UNF	9/16" - 18 UNF	1.50	38.10	1.00	25.40	60,000	414
6YY6-6-9C	3/4" - 16 UNF	1-1/8" - 12 UNF	2.12	53.85	1.12	28.45	60,000	414
6YY6-9-4C	1-1/8" - 12 UNF	9/16" - 18 UNF	1.75	44.45	1.37	34.80	60,000	414
6YY6-9-6C	1-1/8" - 12 UNF	3/4" - 16 UNF	1.87	47.50	1.37	34.80	60,000	414
6YY6-9-9C	1-1/8" - 12 UNF	1-1/8" - 12 UNF	2.26	57.40	1.375	34.93	60,000	414

Y6Y6 — Male High Pressure x Male High Pressure



Part Number	T1 Thread Size	T2 Thread Size	A Overall Length		H Hex		Max. Working Pressure	
			inch	mm	inch	mm	psi	MPa
#								
Y6Y6-4-4C	9/16" - 18 UNF	9/16" - 18 UNF	1.68	42.67	0.62	15.75	60,000	414
Y6Y6-4-6C	9/16" - 18 UNF	3/4" - 16 UNF	2.06	52.32	0.75	19.05	60,000	414
Y6Y6-4-9C	9/16" - 18 UNF	1-1/8" - 12 UNF	2.25	57.15	1.12	28.45	60,000	414
Y6Y6-6-6C	3/4" - 16 UNF	3/4" - 16 UNF	2.25	57.15	0.75	19.05	60,000	414
Y6Y6-6-9C	3/4" - 16 UNF	1-1/8" - 12 UNF	2.50	63.50	1.12	28.45	60,000	414
Y6Y6-9-9C	1-1/8" - 12 UNF	1-1/8" - 12 UNF	2.62	66.55	1.12	28.45	60,000	414

X6Y6 — Low Angle Face Seal x Male High Pressure




Part Number	T1 Thread Size	T2 Thread Size	A Overall Length		H Hex		Max. Working Pressure	
			inch	mm	inch	mm	psi	MPa
#								
X6Y6-6-9C*	9/16"-18 UNF	1-1/8" - 12 UNF	2.00	50.80	1.125	28.58	60,000	414

*Non-standard part - may require longer lead time


High Pressure Adapters

6Y6Y — Female High Pressure, Straight Coupling




Part Number	T1 Thread Size	T2 Thread Size	A Overall Length		H Hex		Max. Working Pressure	
			inch	mm	inch	mm	psi	MPa
#								
6Y6Y-4-4C	9/16" - 18 UNF	9/16" - 18 UNF	1.75	44.45	1.00	25.40	60,000	414
6Y6Y-6-6C	3/4" - 16 UNF	3/4" - 16 UNF	2.00	50.80	1.00	25.40	60,000	414
6Y6Y-9-9C	1-1/8" - 12 UNF	1-1/8" - 12 UNF	2.37	60.20	1.37	34.80	60,000	414

6Y6Y — Female High Pressure, Reducer Coupling



Part Number	T1 Thread Size	T2 Thread Size	A Overall Length		H Hex		Max. Working Pressure	
			inch	mm	inch	mm	psi	MPa
#								
6Y6Y-4-6C	9/16" - 18 UNF	3/4" - 16 UNF	1.62	41.15	1.00	25.40	60,000	414
6Y6Y-4-9C	9/16" - 18 UNF	1-1/8" - 12 UNF	1.75	44.45	1.37	34.80	60,000	414
6Y6Y-6-9C	3/4" - 16 UNF	1-1/8" - 12 UNF	2.00	50.80	1.37	34.80	60,000	414

Y6D9 — Male High Pressure x Male BSP



Part Number	T1 Thread Size	T2 Thread Size	A Overall Length		H Hex		Max. Working Pressure	
			inch	mm	inch	mm	psi	MPa
#								
Y6D9-4-6C	9/16" - 18 UNF	G3/8 - 19	1.57	39.88	0.875	22.23	30,000 *	207*
Y6D9-6-6C	3/4" - 16 UNF	G3/8 - 19	1.85	46.99	0.875	22.23	30,000 *	207*

*BSP connection end lowers working pressure to 30,000psi