



JIC Adapters

K0303— Male JIC x Male JIC




Part Number	T1 Thread Size	T2 Thread Size	A Overall Length		H Hex		Max. Working Pressure	
			inch	mm	inch	mm	psi	MPa
#								
10K0303-4-4C	7/16" - 20 UNF	7/16" - 20 UNF	1.50	38.10	0.625	15.88	10,000	69
10K0303-4-6C	7/16" - 20 UNF	9/16" - 18 UNF	1.50	38.10	0.625	15.88	10,000	69
10K0303-4-8C	7/16" - 20 UNF	3/4" - 16 UNF	1.72	43.69	0.875	22.23	10,000	69
10K0303-6-8C	9/16" - 18 UNF	3/4" - 16 UNF	1.73	43.94	0.875	22.23	10,000	69

K0306— Male JIC x Female JIC



Part Number	T1 Thread Size	T2 Thread Size	A Overall Length		H Hex		Max. Working Pressure	
			inch	mm	inch	mm	psi	MPa
#								
10K0306-4-4C	7/16" - 20 UNF	7/16" - 20 UNF	1.43	36.32	0.75	19.05	10,000	69
10K0306-4-6C	7/16" - 20 UNF	9/16" - 18 UNF	1.55	39.37	0.875	22.23	10,000	69
10K0306-4-8C	7/16" - 20 UNF	3/4" - 16 UNF	1.60	40.64	1.00	25.40	10,000	69
10K0306-6-6C	9/16" - 18 UNF	9/16" - 18 UNF	1.55	39.37	0.875	22.23	10,000	69
10K0306-8-6C	3/4" - 16 UNF	9/16" - 18 UNF	1.55	39.37	0.875	22.23	10,000	69


K0606— Female JIC x Female JIC



Part Number	T1 Thread Size	T2 Thread Size	A Overall Length		H Hex		Max. Working Pressure	
			inch	mm	inch	mm	psi	MPa
#								
10K0606-4-4C	7/16" - 20 UNF	7/16" - 20 UNF	1.35	34.29	0.75	19.05	10,000	69
10K0606-4-6C	7/16" - 20 UNF	9/16" - 18 UNF	1.50	38.10	0.875	22.23	10,000	69
10K0606-6-6C	9/16" - 18 UNF	9/16" - 18 UNF	1.40	35.56	0.875	22.23	10,000	69


JIC Adapters

YA03 — Male Type “M” x Male JIC




Part Number	T1 Thread Size	T2 Thread Size	A Overall Length		H Hex		Max. Working Pressure	
			inch	mm	inch	mm	psi	MPa
#								
YA03-11-6C	1" - 12 UNF	9/16" - 18 UNF	1.69	42.93	1.00	34.93	10,000	103
YA03-16-8C	1-5/16" - 12 UNF	3/4" - 16 UNF	1.79	45.47	1.375	34.93	10,000	103
YA03-16-12C	1-5/16" - 12 UNF	1- 1/16" - 12 UNF	2.00	50.80	1.375	34.93	10,000	69

Y503 — Male Medium Pressure x Male JIC



Part Number	T1 Thread Size	T2 Thread Size	A Overall Length		H Hex		Max. Working Pressure	
			inch	mm	inch	mm	psi	MPa
#								
Y503-4-8C	7/16" - 20 UNF	3/4" - 16 UNF	1.74	44.20	0.875	22.23	15,000	103
Y503-9-10C	13/16" - 16 UNF	7/8" - 14 UNF	2.38	60.45	1.000	25.40	10,000	69
Y503-9-12C	13/16" - 16 UNF	1-1/16" - 12 UNF	2.47	62.74	1.125	28.58	10,000	69
Y503-9-16C	13/16" - 16 UNF	1-5/16" - 12 UNF	2.55	64.77	1.375	34.93	10,000	69
Y503-12-6C	3/4" - 14 NPSM	9/16" - 18 UNF	2.25	57.15	1.125	28.58	15,000	103
Y503-12-8C	3/4" - 14 NPSM	3/4" - 16 UNF	2.35	59.69	1.125	28.58	15,000	103
Y503-12-12C	3/4" - 14 NPSM	1-1/16" - 12 UNF	2.66	67.56	1.125	28.58	10,000	69
Y503-16-12C	1" - 14 UNF LH	1-1/16" - 12 UNF	4.02	102.11	1.125	28.58	10,000	69
Y503-16-16C	1" - 14 UNF LH	1-5/16" - 12 UNF	4.07	103.38	1.375	34.93	10,000	69


Y603 — Male High Pressure x Male JIC






Part Number	T1 Thread Size	T2 Thread Size	A Overall Length		H Hex		Max. Working Pressure	
			inch	mm	inch	mm	psi	MPa
#								
Y603-4-4C	9/16" - 18 UNF	7/16" - 20 UNF	1.61	40.89	0.625	15.88	15,000	103
Y603-4-6C	9/16" - 18 UNF	9/16" - 18 UNF	1.61	40.89	0.625	15.88	15,000	103
Y603-4-8C	9/16" - 18 UNF	3/4" - 16 UNF	1.81	45.97	0.875	22.23	15,000	103
Y603-6-4C	3/4" - 16 UNF	7/16" - 20 UNF	1.84	46.74	0.750	19.05	15,000	103
Y603-6-6C	3/4" - 16 UNF	9/16" - 18 UNF	1.94	49.28	0.750	19.05	15,000	103
Y603-6-8C	3/4" - 16 UNF	3/4" - 16 UNF	2.04	51.82	0.875	22.23	15,000	103
Y603-9-6C	1-1/8" - 12 UNF	9/16" - 18 UNF	2.09	53.09	1.125	28.58	15,000	103
Y603-9-8C	1-1/8" - 12 UNF	3/4" - 16 UNF	2.19	55.63	1.125	28.58	15,000	103


JIC Adapters




JIC Caps



Part Number	Thread Size	Overall Length		Hex		Max. Working Pressure	
		inch	mm	inch	mm	psi	MPa
#							
10K06-4C-CAP	7/16" - 20 UNF	0.83	21.08	0.75	19.05	15,000	103
10K06-6C-CAP	9/16" - 18 UNF	0.93	23.62	0.875	22.23	15,000	103
10K06-8C-CAP	3/4" - 16 UNF	1.04	26.42	1.00	25.40	15,000	103
10K06-10C-CAP	7/8" - 14 UNF	1.16	29.46	1.25	31.75	10,000	69
10K06-12C-CAP	1-1/16" - 12 UNF	1.31	33.27	1.50	38.10	10,000	69

JIC Plugs



Part Number	Thread Size	A Overall Length		Hex		Max. Working Pressure	
		inch	mm	inch	mm	psi	MPa
#							
10KP03-4C	7/16" - 20 UNF	0.81	20.57	0.5	12.70	10,000	69
10KP03-6C	9/16" - 18 UNF	0.85	21.59	0.625	15.88	10,000	69
10KP03-8C	3/4" - 16 UNF	0.95	24.13	0.812	20.62	10,000	69
10KP03-10C	7/8" - 14 UNF	1.11	28.19	0.937	23.80	10,000	69
10KP03-16C	1-5/16" - 12 UNF	1.34	34.04	1.375	34.93	10,000	69