


# Medium Pressure Adapters

## 5YY5 — Female Medium Pressure x Male Medium Pressure




| Part Number | T1 Thread Size  | T2 Thread Size  | A Overall Length |       | H Hex |       | Max. Working Pressure |     |
|-------------|-----------------|-----------------|------------------|-------|-------|-------|-----------------------|-----|
|             |                 |                 | inch             | mm    | inch  | mm    | psi                   | MPa |
| #           |                 |                 |                  |       |       |       |                       |     |
| 5YY5-4-6C   | 7/16" - 20 UNF  | 9/16" - 18 UNF  | 1.75             | 44.45 | 0.75  | 19.05 | 20,000                | 138 |
| 5YY5-4-9C   | 7/16" - 20 UNF  | 13/16" - 16 UNF | 1.87             | 47.50 | 0.87  | 22.10 | 20,000                | 138 |
| 5YY5-4-12C  | 7/16" - 20 UNF  | 3/4" - 14 NPS   | 2.00             | 50.80 | 1.12  | 28.45 | 20,000                | 138 |
| 5YY5-4-16C  | 7/16" - 20 UNF  | 1-3/8" - 12 UNF | 3.00             | 76.20 | 1.00  | 25.40 | 20,000                | 138 |
| 5YY5-6-4C   | 9/16" - 18 UNF  | 7/16" - 20 UNF  | 1.75             | 44.45 | 0.75  | 19.05 | 20,000                | 138 |
| 5YY5-6-9C   | 9/16" - 18 UNF  | 13/16" - 16 UNF | 1.87             | 47.50 | 0.87  | 22.10 | 20,000                | 138 |
| 5YY5-6-12C  | 9/16" - 18 UNF  | 3/4" - 14 NPS   | 2.00             | 50.80 | 1.12  | 28.45 | 20,000                | 138 |
| 5YY5-6-16C* | 9/16" - 18 UNF  | 1-3/8" - 12 UNF | 3.12             | 79.25 | 1.00  | 25.40 | 20,000                | 138 |
| 5YY5-9-4C   | 13/16" - 16 UNF | 7/16" - 20 UNF  | 2.12             | 53.85 | 1.00  | 25.40 | 20,000                | 138 |
| 5YY5-9-6C   | 13/16" - 16 UNF | 9/16" - 18 UNF  | 2.12             | 53.85 | 1.00  | 25.40 | 20,000                | 138 |
| 5YY5-9-12C  | 13/16" - 16 UNF | 9/16" - 18 UNF  | 2.50             | 63.50 | 1.12  | 28.45 | 20,000                | 138 |
| 5YY5-9-16C  | 13/16" - 16 UNF | 1-3/8" - 12 UNF | 3.37             | 85.60 | 1.00  | 25.40 | 20,000                | 138 |
| 5YY5-12-4C* | 3/4" - 14 NPS   | 7/16" - 20 UNF  | 1.25             | 31.75 | 1.37  | 34.80 | 20,000                | 138 |
| 5YY5-12-6C  | 3/4" - 14 NPS   | 9/16" - 18 UNF  | 2.37             | 60.20 | 1.37  | 34.80 | 20,000                | 138 |
| 5YY5-12-9C  | 3/4" - 14 NPS   | 13/16" - 16 UNF | 2.87             | 72.90 | 1.37  | 34.80 | 20,000                | 138 |
| 5YY5-12-16C | 3/4" - 14 NPS   | 1-3/8" - 12 UNF | 3.75             | 95.25 | 1.37  | 34.80 | 20,000                | 138 |
| 5YY5-16-4C  | 1-3/8" - 12 UNF | 7/16" - 20 UNF  | 2.75             | 69.85 | 1.75  | 44.45 | 20,000                | 138 |
| 5YY5-16-6C  | 1-3/8" - 12 UNF | 9/16" - 18 UNF  | 2.87             | 72.90 | 1.75  | 44.45 | 20,000                | 138 |
| 5YY5-16-9C  | 1-3/8" - 12 UNF | 13/16" - 16 UNF | 3.00             | 76.20 | 1.75  | 44.45 | 20,000                | 138 |
| 5YY5-16-12C | 1-3/8" - 12 UNF | 3/4" - 14 NPS   | 3.25             | 82.55 | 1.75  | 44.45 | 20,000                | 138 |

\*Non-standard part - may require longer lead time


# Medium Pressure Adapters

## Y5Y5 — Male Medium Pressure x Male Medium Pressure



| Part Number | T1 Thread Size  | T2 Thread Size  | A Overall Length |        | H Hex |       | Max. Working Pressure |     |
|-------------|-----------------|-----------------|------------------|--------|-------|-------|-----------------------|-----|
|             |                 |                 | inch             | mm     | inch  | mm    | psi                   | MPa |
| #           |                 |                 |                  |        |       |       |                       |     |
| Y5Y5-4-4C   | 7/16" - 20 UNF  | 7/16" - 20 UNF  | 2.00             | 50.80  | 0.62  | 15.75 | 20,000                | 138 |
| Y5Y5-4-6C   | 7/16" - 20 UNF  | 9/16" - 18 UNF  | 2.12             | 53.85  | 0.75  | 19.05 | 20,000                | 138 |
| Y5Y5-4-9C   | 7/16" - 20 UNF  | 13/16" - 16 UNF | 2.18             | 55.37  | 0.875 | 22.23 | 20,000                | 138 |
| Y5Y5-4-12C  | 7/16" - 20 UNF  | 3/4" - 14 NPS   | 2.50             | 63.50  | 1.12  | 28.45 | 20,000                | 138 |
| Y5Y5-4-16C  | 7/16" - 20 UNF  | 1-3/8" - 12 UNF | 3.62             | 91.95  | 1.00  | 25.40 | 20,000                | 138 |
| Y5Y5-6-6C   | 9/16" - 18 UNF  | 9/16" - 18 UNF  | 2.25             | 57.15  | 0.75  | 19.05 | 20,000                | 138 |
| Y5Y5-6-9C   | 9/16" - 18 UNF  | 13/16" - 16 UNF | 2.50             | 63.50  | 0.87  | 22.10 | 20,000                | 138 |
| Y5Y5-6-12C  | 9/16" - 18 UNF  | 3/4" - 14 NPS   | 2.62             | 66.55  | 1.12  | 28.45 | 20,000                | 138 |
| Y5Y5-6-16C  | 9/16" - 18 UNF  | 1-3/8" - 12 UNF | 3.75             | 95.25  | 1.00  | 25.40 | 20,000                | 138 |
| Y5Y5-9-9C   | 13/16" - 16 UNF | 13/16" - 16 UNF | 2.50             | 63.50  | 1.00  | 25.40 | 20,000                | 138 |
| Y5Y5-9-12C  | 13/16" - 16 UNF | 3/4" - 14 NPS   | 2.87             | 72.90  | 1.12  | 28.45 | 20,000                | 138 |
| Y5Y5-9-16C  | 13/16" - 16 UNF | 1-3/8" - 12 UNF | 4.00             | 101.60 | 1.00  | 25.40 | 20,000                | 138 |
| Y5Y5-12-12C | 3/4" - 14 NPS   | 3/4" - 14 NPS   | 3.00             | 76.20  | 1.12  | 28.45 | 20,000                | 138 |
| Y5Y5-12-16C | 3/4" - 14 NPS   | 1-3/8" - 12 UNF | 1.25             | 31.75  | 1.12  | 28.45 | 20,000                | 138 |
| Y5Y5-16-16C | 1-3/8" - 12 UNF | 1-3/8" - 12 UNF | 4.25             | 107.95 | 1.375 | 34.93 | 20,000                | 138 |

## 6YY5 — Female High Pressure x Male Medium Pressure




| Part Number | T1 Thread Size  | T2 Thread Size  | A Overall Length |       | H Hex |       | Max. Working Pressure |     |
|-------------|-----------------|-----------------|------------------|-------|-------|-------|-----------------------|-----|
|             |                 |                 | inch             | mm    | inch  | mm    | psi                   | MPa |
| #           |                 |                 |                  |       |       |       |                       |     |
| 6YY5-4-4C   | 9/16" - 18 UNF  | 7/16" - 20 UNF  | 1.75             | 44.45 | 0.75  | 19.05 | 20,000                | 138 |
| 6YY5-4-6C   | 9/16" - 18 UNF  | 9/16" - 18 UNF  | 1.75             | 44.45 | 0.75  | 19.05 | 20,000                | 138 |
| 6YY5-4-9C   | 9/16" - 18 UNF  | 13/16" - 16 UNF | 1.87             | 47.50 | 0.87  | 22.10 | 20,000                | 138 |
| 6YY5-4-12C* | 9/16" - 18 UNF  | 3/4" - 14 NPS   | 2.25             | 57.15 | 1.12  | 28.45 | 20,000                | 138 |
| 6YY5-4-16C  | 9/16" - 18 UNF  | 1-3/8" - 12 UNF | 3.00             | 76.20 | 1.00  | 25.40 | 20,000                | 138 |
| 6YY5-6-4C   | 3/4" - 16 UNF   | 7/16" - 20 UNF  | 1.87             | 47.50 | 1.00  | 25.40 | 20,000                | 138 |
| 6YY5-6-6C   | 3/4" - 16 UNF   | 9/16" - 18 UNF  | 1.87             | 47.50 | 1.00  | 25.40 | 20,000                | 138 |
| 6YY5-6-9C*  | 3/4" - 16 UNF   | 13/16" - 16 UNF | 2.00             | 50.80 | 1.00  | 25.40 | 20,000                | 138 |
| 6YY5-6-12C  | 3/4" - 16 UNF   | 3/4" - 14 NPS   | 2.25             | 57.15 | 1.12  | 28.45 | 20,000                | 138 |
| 6YY5-6-16C  | 3/4" - 16 UNF   | 1-3/8" - 12 UNF | 3.25             | 82.55 | 1.00  | 25.40 | 20,000                | 138 |
| 6YY5-9-4C   | 1-1/8" - 12 UNF | 7/16" - 20 UNF  | 2.12             | 53.85 | 1.37  | 34.80 | 20,000                | 138 |
| 6YY5-9-6C*  | 1-1/8" - 12 UNF | 9/16" - 18 UNF  | 2.12             | 53.85 | 1.37  | 34.80 | 20,000                | 138 |
| 6YY5-9-9C   | 1-1/8" - 12 UNF | 13/16" - 16 UNF | 2.37             | 60.20 | 1.37  | 34.80 | 20,000                | 138 |
| 6YY5-9-12C  | 1-1/8" - 12 UNF | 3/4" - 14 NPS   | 2.50             | 63.50 | 1.37  | 34.80 | 20,000                | 138 |
| 6YY5-9-16C  | 1-1/8" - 12 UNF | 1-3/8" - 12 UNF | 3.62             | 91.95 | 1.37  | 34.80 | 20,000                | 138 |

\*Non-standard part - may require longer lead time

# Medium Pressure Adapters

## 5YY6 — Female Medium Pressure x Male High Pressure




| Part Number | T1 Thread Size  | T2 Thread Size  | A Overall Length |       | H Hex |       | Max. Working Pressure |     |
|-------------|-----------------|-----------------|------------------|-------|-------|-------|-----------------------|-----|
|             |                 |                 | inch             | mm    | inch  | mm    | psi                   | MPa |
| #           |                 |                 |                  |       |       |       |                       |     |
| 5YY6-4-4C   | 7/16" - 20 UNF  | 9/16" - 18 UNF  | 1.37             | 34.80 | 0.75  | 19.05 | 20,000                | 138 |
| 5YY6-4-6C   | 7/16" - 20 UNF  | 3/4" - 16 UNF   | 1.75             | 44.45 | 0.75  | 19.05 | 20,000                | 138 |
| 5YY6-4-9C   | 7/16" - 20 UNF  | 1-1/8" - 12 UNF | 2.12             | 53.85 | 1.12  | 28.45 | 20,000                | 138 |
| 5YY6-6-4C   | 9/16" - 18 UNF  | 9/16" - 18 UNF  | 1.75             | 44.45 | 0.75  | 19.05 | 20,000                | 138 |
| 5YY6-6-6C   | 9/16" - 18 UNF  | 3/4" - 16 UNF   | 1.75             | 44.45 | 0.75  | 19.05 | 20,000                | 138 |
| 5YY6-6-9C   | 9/16" - 18 UNF  | 1-1/8" - 12 UNF | 2.12             | 53.85 | 1.12  | 28.45 | 20,000                | 138 |
| 5YY6-9-4C   | 13/16" - 16 UNF | 9/16" - 18 UNF  | 1.87             | 47.50 | 1.00  | 25.40 | 20,000                | 138 |
| 5YY6-9-6C   | 13/16" - 16 UNF | 3/4" - 16 UNF   | 2.12             | 53.85 | 1.00  | 25.40 | 20,000                | 138 |
| 5YY6-9-9C   | 13/16" - 16 UNF | 1-1/8" - 12 UNF | 2.12             | 53.85 | 1.12  | 28.45 | 20,000                | 138 |
| 5YY6-12-4C  | 3/4" - 14 NPS   | 9/16" - 18 UNF  | 2.50             | 63.50 | 1.37  | 34.80 | 20,000                | 138 |
| 5YY6-12-6C  | 3/4" - 14 NPS   | 3/4" - 16 UNF   | 2.37             | 60.20 | 1.37  | 34.80 | 20,000                | 138 |
| 5YY6-12-9C  | 3/4" - 14 NPS   | 1-1/8" - 12 UNF | 2.62             | 66.55 | 1.37  | 34.80 | 20,000                | 138 |
| 5YY6-16-4C* | 1-3/8" - 12 UNF | 9/16" - 18 UNF  | 2.62             | 66.55 | 1.75  | 44.45 | 20,000                | 138 |
| 5YY6-16-6C* | 1-3/8" - 12 UNF | 3/4" - 16 UNF   | 2.87             | 72.90 | 1.75  | 44.45 | 20,000                | 138 |
| 5YY6-16-9C  | 1-3/8" - 12 UNF | 1-1/8" - 12 UNF | 3.12             | 79.25 | 1.75  | 44.45 | 20,000                | 138 |

\*Non-standard part - may require longer lead time

# Medium Pressure Adapters


## Y5Y6 — Male Medium Pressure x Male High Pressure



| Part Number | T1 Thread Size  | T2 Thread Size  | A Overall Length |        | H Hex |       | Max. Working Pressure |     |
|-------------|-----------------|-----------------|------------------|--------|-------|-------|-----------------------|-----|
|             |                 |                 | inch             | mm     | inch  | mm    | psi                   | MPa |
| #           |                 |                 |                  |        |       |       |                       |     |
| Y5Y6-4-4C   | 7/16" - 20 UNF  | 9/16" - 18 UNF  | 1.73             | 43.94  | 0.63  | 16.00 | 20,000                | 138 |
| Y5Y6-4-6C   | 7/16" - 20 UNF  | 3/4" - 16 UNF   | 2.10             | 53.34  | 0.75  | 19.05 | 20,000                | 138 |
| Y5Y6-4-9C   | 7/16" - 20 UNF  | 1-1/8" - 12 UNF | 2.37             | 60.20  | 1.12  | 28.45 | 20,000                | 138 |
| Y5Y6-6-4C   | 9/16" - 18 UNF  | 9/16" - 18 UNF  | 2.12             | 53.85  | 0.62  | 15.75 | 20,000                | 138 |
| Y5Y6-6-9C   | 9/16" - 18 UNF  | 1-1/8" - 12 UNF | 2.50             | 63.50  | 1.12  | 28.45 | 20,000                | 138 |
| Y5Y6-9-4C   | 13/16" - 16 UNF | 9/16" - 18 UNF  | 2.25             | 57.15  | 0.87  | 22.10 | 20,000                | 138 |
| Y5Y6-9-6C   | 13/16" - 16 UNF | 3/4" - 16 UNF   | 2.38             | 60.45  | 0.875 | 22.23 | 20,000                | 138 |
| Y5Y6-9-9C   | 13/16" - 16 UNF | 1-1/8" - 12 UNF | 2.62             | 66.55  | 1.12  | 28.45 | 20,000                | 138 |
| Y5Y6-12-4C  | 3/4" - 14 NPS   | 9/16" - 18 UNF  | 2.62             | 66.55  | 1.12  | 28.45 | 20,000                | 138 |
| Y5Y5-12-6C* | 3/4" - 14 NPS   | 3/4" - 16 UNF   | 2.75             | 69.85  | 1.12  | 28.45 | 20,000                | 138 |
| Y5Y6-12-9C  | 3/4" - 14 NPS   | 1-1/8" - 12 UNF | 3.00             | 76.20  | 1.12  | 28.45 | 20,000                | 138 |
| Y5Y6-16-4C* | 1-3/8" - 12 UNF | 9/16" - 18 UNF  | 3.62             | 91.95  | 1.00  | 25.40 | 20,000                | 138 |
| Y5Y6-16-6C* | 1-3/8" - 12 UNF | 3/4" - 16 UNF   | 4.00             | 101.60 | 1.00  | 25.40 | 20,000                | 138 |
| Y5Y6-16-9C  | 1-3/8" - 12 UNF | 1-1/8" - 12 UNF | 4.00             | 101.60 | 1.12  | 28.45 | 20,000                | 138 |

\*Non-standard part - may require longer lead time


## Y5D9 — Male Medium Pressure x Male BSP



| Part Number | T1 Thread Size  | T2 Thread Size | A Overall Length |       | H Hex |       | Max. Working Pressure |     |
|-------------|-----------------|----------------|------------------|-------|-------|-------|-----------------------|-----|
|             |                 |                | inch             | mm    | inch  | mm    | psi                   | MPa |
| #           |                 |                |                  |       |       |       |                       |     |
| Y5D9-4-4C   | 7/16" - 20 UNF  | G1/4 - 19      | 1.47             | 37.34 | 0.75  | 19.05 | 20,000                | 138 |
| Y5D9-6-4C   | 9/16" - 18 UNF  | G1/4 - 19      | 1.69             | 42.93 | 0.75  | 19.05 | 20,000                | 138 |
| Y5D9-6-6C   | 9/16" - 18 UNF  | G3/8 - 19      | 1.66             | 42.16 | 0.875 | 22.23 | 20,000                | 138 |
| Y5D9-9-6C   | 13/16" - 16 UNF | G3/8 - 19      | 1.88             | 47.75 | 0.875 | 22.23 | 20,000                | 138 |


# Medium Pressure Adapters

## 5Y5Y — Female Medium Pressure, Straight Coupling



| Part Number | T1 Thread Size  | T2 Thread Size  | A Overall Length |       | H Hex |       | Max. Working Pressure |     |
|-------------|-----------------|-----------------|------------------|-------|-------|-------|-----------------------|-----|
|             |                 |                 | inch             | mm    | inch  | mm    | psi                   | MPa |
| #           |                 |                 |                  |       |       |       |                       |     |
| 5Y5Y-4-4C   | 7/16" - 20 UNF  | 7/16" - 20 UNF  | 1.62             | 41.15 | 0.75  | 19.05 | 20,000                | 138 |
| 5Y5Y-6-6C   | 9/16" - 18 UNF  | 9/16" - 18 UNF  | 1.75             | 44.45 | 0.75  | 19.05 | 20,000                | 138 |
| 5Y5Y-9-9C   | 13/16" - 16 UNF | 13/16" - 16 UNF | 2.12             | 53.85 | 1.00  | 25.40 | 20,000                | 138 |
| 5Y5Y-12-12C | 3/4" - 14 NPS   | 3/4" - 14 NPS   | 2.50             | 63.50 | 1.37  | 34.80 | 20,000                | 138 |
| 5Y5Y-16-16C | 1-3/8" - 12 UNF | 1-3/8" - 12 UNF | 3.50             | 88.90 | 1.75  | 44.45 | 20,000                | 138 |

## 5Y5Y — Female Medium Pressure, Reducer Coupling




| Part Number | T1 Thread Size  | T2 Thread Size  | A Overall Length |       | H Hex |       | Max. Working Pressure |     |
|-------------|-----------------|-----------------|------------------|-------|-------|-------|-----------------------|-----|
|             |                 |                 | inch             | mm    | inch  | mm    | psi                   | MPa |
| #           |                 |                 |                  |       |       |       |                       |     |
| 5Y5Y-4-6C   | 7/16" - 20 UNF  | 9/16" - 18 UNF  | 1.75             | 44.45 | 0.75  | 19.05 | 20,000                | 138 |
| 5Y5Y-4-9C   | 7/16" - 20 UNF  | 13/16" - 16 UNF | 2.12             | 53.85 | 1.00  | 25.40 | 20,000                | 138 |
| 5Y5Y-4-12C* | 7/16" - 20 UNF  | 3/4" - 14 NPS   | 2.50             | 63.50 | 1.37  | 34.80 | 20,000                | 138 |
| 5Y5Y-4-16C  | 7/16" - 20 UNF  | 1-3/8" - 12 UNF | 3.50             | 88.90 | 1.75  | 44.45 | 20,000                | 138 |
| 5Y5Y-6-9C   | 9/16" - 18 UNF  | 13/16" - 16 UNF | 2.12             | 53.85 | 1.00  | 25.40 | 20,000                | 138 |
| 5Y5Y-6-12C  | 9/16" - 18 UNF  | 3/4" - 14 NPS   | 2.50             | 63.50 | 1.37  | 34.80 | 20,000                | 138 |
| 5Y5Y-6-16C  | 9/16" - 18 UNF  | 1-3/8" - 12 UNF | 3.50             | 88.90 | 1.75  | 44.45 | 20,000                | 138 |
| 5Y5Y-9-12C  | 13/16" - 16 UNF | 3/4" - 14 NPS   | 2.50             | 63.50 | 1.37  | 34.80 | 20,000                | 138 |
| 5Y5Y-9-16C  | 13/16" - 16 UNF | 1-3/8" - 12 UNF | 3.50             | 88.90 | 1.75  | 44.45 | 20,000                | 138 |
| 5Y5Y-12-16C | 3/4" - 14 NPS   | 1-3/8" - 12 UNF | 3.50             | 88.90 | 1.75  | 44.45 | 20,000                | 138 |

\*Non-standard part - may require longer lead time

# Medium Pressure Adapters

## 5Y6Y — Female Medium Pressure x Female High Pressure Coupling



| Part Number | T1 Thread Size  | T2 Thread Size  | A Overall Length |       | H Hex |       | Max. Working Pressure |     |
|-------------|-----------------|-----------------|------------------|-------|-------|-------|-----------------------|-----|
|             |                 |                 | inch             | mm    | inch  | mm    | psi                   | MPa |
| #           |                 |                 |                  |       |       |       |                       |     |
| 5Y6Y-4-4C   | 7/16" - 20 UNF  | 9/16" - 18 UNF  | 1.62             | 41.15 | 0.75  | 19.05 | 20,000                | 138 |
| 5Y6Y-4-6C   | 7/16" - 20 UNF  | 3/4" - 16 UNF   | 1.87             | 47.50 | 1.00  | 25.40 | 20,000                | 138 |
| 5Y6Y-4-9C*  | 7/16" - 20 UNF  | 1-1/8" - 12 UNF | 2.37             | 60.20 | 1.37  | 34.80 | 20,000                | 138 |
| 5Y6Y-6-4C   | 9/16" - 18 UNF  | 9/16" - 18 UNF  | 1.75             | 44.45 | 0.75  | 19.05 | 20,000                | 138 |
| 5Y6Y-6-6C   | 9/16" - 18 UNF  | 3/4" - 16 UNF   | 1.87             | 47.50 | 1.00  | 25.40 | 20,000                | 138 |
| 5Y6Y-6-9C   | 9/16" - 18 UNF  | 1-1/8" - 12 UNF | 2.37             | 60.20 | 1.37  | 34.80 | 20,000                | 138 |
| 5Y6Y-9-4C   | 13/16" - 16 UNF | 9/16" - 18 UNF  | 2.12             | 53.85 | 1.00  | 25.40 | 20,000                | 138 |
| 5Y6Y-9-6C   | 13/16" - 16 UNF | 3/4" - 16 UNF   | 2.37             | 60.20 | 1.00  | 25.40 | 20,000                | 138 |
| 5Y6Y-9-9C   | 13/16" - 16 UNF | 1-1/8" - 12 UNF | 1.75             | 44.45 | 1.37  | 34.80 | 20,000                | 138 |
| 5Y6Y-12-4C  | 3/4" - 14 NPS   | 9/16" - 18 UNF  | 2.50             | 63.50 | 1.37  | 34.80 | 20,000                | 138 |
| 5Y6Y-12-6C* | 3/4" - 14 NPS   | 3/4" - 16 UNF   | 2.50             | 63.50 | 1.37  | 34.80 | 20,000                | 138 |
| 5Y6Y-12-9C  | 3/4" - 14 NPS   | 1-1/8" - 12 UNF | 2.50             | 63.50 | 1.37  | 34.80 | 20,000                | 138 |
| 5Y6Y-16-4C  | 1-3/8" - 12 UNF | 9/16" - 18 UNF  | 3.50             | 88.90 | 1.37  | 34.80 | 20,000                | 138 |
| 5Y6Y-16-6C* | 1-3/8" - 12 UNF | 3/4" - 16 UNF   | 3.50             | 88.90 | 1.37  | 34.80 | 20,000                | 138 |
| 5Y6Y-16-9C  | 1-3/8" - 12 UNF | 1-1/8" - 12 UNF | 3.50             | 88.90 | 1.37  | 34.80 | 20,000                | 138 |

\*Non-standard part - may require longer lead time